

LITH EX



Technical Specifications of AVD Range



1 L



2 L



6 L



9 L

Extinguisher AVD Type	LITH EX 1 L	LITH EX 2 L	LITH EX 6 L	LITH EX 9 L
Brim Full Capacity (ml)	1,240	2,520	7,780	11,325
Fill Volume AVD Agent (ml)	1,000	2,000	6,000	9,000
Approx. Weight Agent (kg)	1.1	2.2	6.6	9.9
Approx. weight of Unit (kg)	2.1	3.9	10.7	15.0
Cylinder Ø (mm)	85	110	170	170
Cylinder Height (mm)	320	380	522	664
Unit Height (mm)	350	410	530	672
Handle	Metal - Red	Metal - Red	Metal - Red	Metal - Red
Hose	N/A	N/A	Yes with Magnet	Yes with Magnet
Base	Integral Base & Wall Bracket	Integral Base & Wall Bracket	Green PP	Green PP
Bracket			Wall Hanger	Wall Hanger
Fire Rating	3A	5A	13A	13A
EN3 Certified	Not Allowed	Yes	Yes	Yes
Propellant	Nitrogen (3% He)	Nitrogen (3% He)	Nitrogen (3% He)	Nitrogen (3% He)
Operating Pressure (bar) *	15	15	15	15
Operating Temperature (°C)	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C
Approx. Discharge Time (s)	25	50	120	180
Discharge Range (m)	1.5 - 2.0	1.5 - 2.0	1.5 - 2.0	1.5 - 2.0
Packaged Unit (l x w x h) (mm)	102 x 104 x 360	125 x 128 x 420	197 x 267 x 525	199 x 226 x 670
Units per Box	10	6	1	1
Box Dimensions (mm)	394 x 535 x 226	444 x 392 x 265	N/A	N/A

* Pressure refers to gauge pressure

Dupré Minerals Ltd

Spencroft Road, Newcastle-under-Lyme, Staffordshire, ST5 9JE, UK

Tel: +44 (0)1782 383124

avd@goodwingroup.com

www.avdfire.com

Rev 8 06/10/2020